UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/511,238	09/19/2005	Nae Hyuck Chang	51876P723	1833
8791 7590 12/21/2009 BLAKELY SOKOLOFF TAYLOR & ZAFMAN LLP			EXAMINER	
1279 OAKMEAD PARKWAY			SIM, YONG H	
SUNNY VALE,	SUNNYVALE, CA 94085-4040		ART UNIT	PAPER NUMBER
			2629	
			MAIL DATE	DELIVERY MODE
			12/21/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)		
	10/511,238	CHANG ET AL.		
Office Action Summary	Examiner	Art Unit		
	YONG SIM	2629		
The MAILING DATE of this communication appeariod for Reply	ppears on the cover sheet with	the correspondence address		
A SHORTENED STATUTORY PERIOD FOR REP WHICHEVER IS LONGER, FROM THE MAILING I - Extensions of time may be available under the provisions of 37 CFR 1 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory perio - Failure to reply within the set or extended period for reply will, by statu. Any reply received by the Office later than three months after the mail earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICA 1.136(a). In no event, however, may a repl d will apply and will expire SIX (6) MONTH tte, cause the application to become ABAN	ATION. y be timely filed IS from the mailing date of this communication. IDONED (35 U.S.C. § 133).		
Status				
1) ■ Responsive to communication(s) filed on 22 2a) ■ This action is FINAL . 2b) ■ Th 3) ■ Since this application is in condition for allow closed in accordance with the practice under	is action is non-final. ance except for formal matter			
Disposition of Claims				
4) Claim(s) 15-26 is/are pending in the application 4a) Of the above claim(s) is/are withdr 5) Claim(s) is/are allowed. 6) Claim(s) 15-26 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/	awn from consideration.			
Application Papers				
9) The specification is objected to by the Examir 10) The drawing(s) filed on is/are: a) according a deposition of the deposition and applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Examing the specific and the specif	ccepted or b) objected to by e drawing(s) be held in abeyance ection is required if the drawing(s)	e. See 37 CFR 1.85(a). is objected to. See 37 CFR 1.121(d).		
Priority under 35 U.S.C. § 119				
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 				
Attachment(s)	_			
 Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date 	Paper No(s)/l	nmary (PTO-413) Mail Date rmal Patent Application		

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 9/22/2009 has been entered.

Response to Arguments

2. Applicant's arguments with respect to claims 15 – 26 have been considered but are most in view of the new ground(s) of rejection.

With respect to the Applicant's argument regarding claim 1, the Applicant argues that Cui does not teach "structured display capability information that includes backlight luminance information as a sub-element of the display capability information."

However, Examiner respectfully disagrees. Examiner respectfully asserts that the backlight luminance information must be provided in step 606 of Fig. 6. A software program controls the display image brightness and display backlight brightness. The control cannot be accomplished without such backlight information included as a sub-element. Please refer to the rejection below.

Art Unit: 2629

Therefore, the argument is moot.

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. The factual inquiries set forth in *Graham* v. *John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:
 - 1. Determining the scope and contents of the prior art.
 - 2. Ascertaining the differences between the prior art and the claims at issue.
 - 3. Resolving the level of ordinary skill in the pertinent art.
 - 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.
- 3. Claims 15 22 are rejected under 35 U.S.C. 103(a) as being anticipated by Cui (US 2003/0001815 A1) in view of Croney et al. (Hereinafter "Croney" US 2004/0073873 A1).

Re claim 15, Cui teaches a visual data adaptation method comprising: adapting visual data in response to received first display capability information of a display device in a first user terminal and a usage environment of the particular user terminal (Para 0037; "If a color segment brightness level exceeds or falls below the respective

Art Unit: 2629

segment threshold/display capability by a certain amount, this information is relayed to a software program, which determines whether the display image brightness or backlight brightness should be adjusted." The display capability information is the information used to maintain a pre-determined display image quality. The particular user terminal is where the display device as shown in Fig. 1. Para 0038; "an ambient light sensor is used to determined the brightness of ambient light surrounding a display monitor, in which the display image will be display. The image may then be adjusted to account for ambient light brightness.");

Page 4

and outputting the first adapted visual data to the particular user terminal, wherein the display capability information is hierarchically structured to include backlight luminance information as a sub-element of the display capability information (Para 0037; "when a color brightness level exceeds or falls below a threshold by an amount, an interrupt is generated causing a software program to either program the graphics gamma unit to adjust the display image brightness or enable the PWM to adjust the display backlight brightness in order to maintain a pre-determined display image quality." In order to maintain the pre-determined display image quality, which is the display capability, the software program must contain both the display image brightness and the backlight brightness information as sub-elements to dynamically adjust the image brightness.), and the backlight luminance information is described as a numerical value ranging from a lowest possible value to a highest possible value that is adjusted according to the usage environment of the particular user terminal (Para 0037; "if a target display image quality can be achieved by adjusting the backlight brightness while

maintaining a target display device power target, then the PWM will be programmed accordingly. Otherwise, the target display image quality will be achieved by adjusting the display image brightness." The adjustment of the backlight brightness is conducted by a program wherein the backlight brightness is described digitally in numerical values. The range of the backlight brightness information is determined by the target display image quality described above. In other words, if the highest possible value of the backlight is not sufficient, the software program will relay the information to adjust the image data.).

But does not expressly teach adapting the visual data in response to received second display capability information of a second display device in a second user terminal and providing a single source, multi-use environment, where one content is adapted to and used in different usage environments.

However, Croney teaches a method for rendering images for display on client devices wherein an image or images having the appropriate size and format compatible with each client device based on the capabilities and environment associated with the particular client device is generated from a single source image (Croney: Para 0009).

Therefore, taking the combined teachings of Cui and Croney, as a whole, it would have been obvious to a person having ordinary skill in the art to incorporate the idea of renderings images on a plurality of client devices wherein images having the appropriate size and format compatible with each client device based on the capabilities associated with the particular client device is generated from a single source image as taught by Croney into the visual data adaptation method of Cui to obtain the method of

Art Unit: 2629

adapting visual data in response to received display capability information of a plurality of display devices including a first and a second display in separate user terminals to adept a single-source content be used in different usage environments to allow a single source content to be properly displayed on a multiple client devices automatically.

Re claim 16, Cui teaches wherein the visual data is RGB data of pixels (Para 0035; "The graphics gamma unit effects the brightness of an image to be displayed on a display monitor by scaling each sub-pixel color." The sub-pixel color data are RGB data.).

Re claim 17, Cui teaches wherein the adaptation is to control pixel value of the visual data according to the backlight luminance information by shifting an RGB value (Para 0035; "The graphics gamma unit effects the brightness of an image to be displayed on a display monitor by scaling each sub-pixel color." Scaling the sub-pixel color value is equivalent to shifting and RGB value.).

Re claim 18, the combined teachings of Cui and Croney teaches the visual data adaptation method as recited in claim 15, wherein the backlight luminance information is adjusted according to the adjusted visual data transmitted from the separate user terminal (Para 0037; "other decision algorithms may be used to determine whether a display image brightness should be changed or backlight brightness should be modified in order to achieve or maintain an image quality while achieving or maintaining a power-

Application/Control Number: 10/511,238

Art Unit: 2629

consumption target." The adjustment of the backlight brightness is conducted by a program according to the adjusted visual data. After adjusting the visual data, further adjustment is necessary to maintain the image quality, the backlight brightness will be adjusted. The software will dynamically adjust both the visual data and the backlight brightness as the threshold of the image quality necessitates them.).

Page 7

Re claim 19, Cui teaches a visual data adaptation apparatus comprising: an adaptation means for adapting visual data in response to received display capability information of a first display device in a first user terminal and a usage environment of the particular user terminal (Para 0037; "If a color segment brightness level exceeds or falls below the respective segment threshold/display capability by a certain amount, this information is relayed to a software program, which determines whether the display image brightness or backlight brightness should be adjusted." The display capability information is the information used to maintain a pre-determined display image quality. The user terminal is where the display device as shown in Fig. 1. The adaptation means is the system as shown in Fig. 1. Para 0038; "an ambient light sensor is used to determined the brightness of ambient light surrounding a display monitor, in which the display image will be display. The image may then be adjusted to account for ambient light brightness."); and an outputting means for outputting the first adapted visual data to the particular user terminal, wherein the display capability information is hierarchically structured to include backlight luminance information as a sub-element of the display capability information (Para 0037; "when a color brightness level exceeds or falls below

a threshold by an amount, an interrupt is generated causing a software program to either program the graphics gamma unit to adjust the display image brightness or enable the PWM to adjust the display backlight brightness in order to maintain a predetermined display image quality." In order to maintain the pre-determined display image quality, which is the display capability, the software program must contain both the display image brightness and the backlight brightness information as sub-elements to dynamically adjust the image brightness.), and the backlight luminance information is described as a numerical value ranging from the lowest possible value to the highest possible value that is adjusted according to the usage environment of the particular user terminal (Para 0037; "if a target display image quality can be achieved by adjusting the backlight brightness while maintaining a target display device power target, then the PWM will be programmed accordingly. Otherwise, the target display image quality will be achieved by adjusting the display image brightness." The adjustment of the backlight brightness is conducted by a program wherein the backlight brightness is described digitally in numerical values. The range of the backlight brightness information is determined by the target display image quality described above. In other words, if the highest possible value of the backlight is not sufficient, the software program will relay the information to adjust the image data.).

But does not expressly teach adapting the visual data in response to received second display capability information of a second display device in a second user terminal and providing a single source, multi-use environment, where one content is adapted to and used in different usage environments.

However, Croney teaches a method for rendering images for display on client devices wherein an image or images having the appropriate size and format compatible with each client device based on the capabilities and environment associated with the particular client device is generated from a single source image (Croney: Para 0009).

Therefore, taking the combined teachings of Cui and Croney, as a whole, it would have been obvious to a person having ordinary skill in the art to incorporate the idea of renderings images on a plurality of client devices wherein images having the appropriate size and format compatible with each client device based on the capabilities associated with the particular client device is generated from a single source image as taught by Croney into the visual data adaptation apparatus of Cui to obtain a visual data adaptation apparatus to adapt visual data in response to received display capability information of a plurality of display devices including a first and a second display in separate user terminals to adept a single-source content be used in different usage environments to allow a single source content to be properly displayed on a multiple client devices automatically.

The limitations of claim 20 are substantially similar to the limitations of claim 16.

Therefore, it has been analyzed and rejected substantially similar to claim 16.

The limitations of claim 21 are substantially similar to the limitations of claim 17.

Therefore, it has been analyzed and rejected substantially similar to claim 17.

Art Unit: 2629

The limitations of claim 22 are substantially similar to the limitations of claim 18. Therefore, it has been analyzed and rejected substantially similar to claim 18.

1. Claims 23 – 26 are rejected under 35 U.S.C. 103(a) as being unpatentable over Cui in view of Croney, as applied to claims 15 - 22 above, and further in view of MacPhail (US 6,593,943 B1).

Re claim 23, Cui teaches a computer readable storage medium in which data is recorded, the data comprising: first display capability information of a first display device in a user terminal (Para 0037; "If a color segment brightness level exceeds or falls below the respective segment threshold/display capability by a certain amount, this information/data is relayed to a software program, which determines whether the display image brightness or backlight brightness should be adjusted." The display capability information is the information used to maintain a pre-determined display image quality. The user terminal is where the display device as shown in Fig. 1. The adaptation means is the system as shown in Fig. 1. The data must be stored in a memory which is processor/computer readable storage medium.), wherein visual data is adapted by a video adaptation apparatus (The adaptation apparatus is a part of the system which uses a software to adjust visual data as shown in Fig. 1.) that is particular from the user terminal (As can be seen in Fig. 1, the system and the display device in a user terminal are particular to each other.) according to the display capability information and a usage

Application/Control Number: 10/511,238

Page 11

Art Unit: 2629

environment of the particular user terminal (Para 0038; "an ambient light sensor is used to determined the brightness of ambient light surrounding a display monitor, in which the display image will be display. The image may then be adjusted to account for ambient light brightness.") the display capability information is hierarchically structured to include backlight luminance information as a sub-element of the display capability information (Para 0037; "when a color brightness level exceeds or falls below a threshold by an amount, an interrupt is generated causing a software program to either program the graphics gamma unit to adjust the display image brightness or enable the PWM to adjust the display backlight brightness in order to maintain a pre-determined display image quality." In order to maintain the pre-determined display image quality, which is the display capability, the software program must contain both the display image brightness and the backlight brightness information as sub-elements to dynamically adjust the image brightness.), and the backlight luminance information is described as a numerical value ranging from the lowest possible value to the highest possible value that is adjusted according to the usage environment of the particular user terminal (Para 0037; "if a target display image quality can be achieved by adjusting the backlight brightness while maintaining a target display device power target, then the PWM will be programmed accordingly. Otherwise, the target display image quality will be achieved by adjusting the display image brightness." The adjustment of the backlight brightness is conducted by a program wherein the backlight brightness is described digitally in numerical values. The range of the backlight brightness information is determined by the target display image quality described above. In other words, if the highest possible

Art Unit: 2629

value of the backlight is not sufficient, the software program will relay the information to adjust the image data.).

But does not expressly teach adapting the visual data in response to received second display capability information of a second display device in a second user terminal and providing a single source, multi-use environment, where one content is adapted to and used in different usage environments.

However, Croney teaches a method for rendering images for display on client devices wherein an image or images having the appropriate size and format compatible with each client device based on the capabilities and environment associated with the particular client device is generated from a single source image (Croney: Para 0009).

Therefore, taking the combined teachings of Cui and Croney, as a whole, it would have been obvious to a person having ordinary skill in the art to incorporate the idea of renderings images on a plurality of client devices wherein images having the appropriate size and format compatible with each client device based on the capabilities associated with the particular client device is generated from a single source image as taught by Croney into t the computer readable storage medium comprising display capability information of display device in a user terminal of Cui to obtain a computer readable storage medium comprising a visual data adaptation apparatus wherein the apparatus to adapt visual data in response to received display capability information of a plurality of display devices including a first and a second display in separate user terminals to adept a single-source content be used in different usage environments to

allow a single source content to be properly displayed on a multiple client devices automatically.

But does not expressly disclose said metadata.

However, MacPhail teaches a method for displaying computer-based information including detecting an instruction to display an information unit based on the data and or metadata stored in storage medium (MacPhail: Col. 10, line 63 – Col 11 line 34).

Therefore, taking the combined teachings of Cui, Croney and MacPhail, as a whole, it would have been obvious to a person having ordinary skill in the art to incorporate the idea of displaying information based on metadata as taught by MacPhail into the computer readable storage medium as taught by Cui and Croney to obtain a computer readable storage medium in which metadata is recorded wherein the metadata comprises display capability information of a display device to adapt visual data according to the display capability information in an efficient was since the metadata can travel along with other data such as video data.

The limitations of claim 24 are substantially similar to the limitations of claim 16.

Therefore, it has been analyzed and rejected substantially similar to claim 16.

The limitations of claim 25 are substantially similar to the limitations of claim 17.

Therefore, it has been analyzed and rejected substantially similar to claim 17.

Art Unit: 2629

The limitations of claim 26 are substantially similar to the limitations of claim 18.

Therefore, it has been analyzed and rejected substantially similar to claim 18.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to YONG SIM whose telephone number is (571)270-1189. The examiner can normally be reached on Monday - Friday (Alternate Fridays off) 7:30-5:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Amr Awad can be reached on (571) 272-7764. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/YONG SIM/ Examiner, Art Unit 2629

Art Unit: 2629

/Amr Awad/ Supervisory Patent Examiner, Art Unit 2629

12/16/2009